

# Specifications

## Range & Wall Oven Features and Specifications

	Electric Ranges		Combination Ranges			All Gas Ranges		Electric Wall Oven
	1850	1855	1865	1870	1875	1860	1867	1880
Range Widths	30 1/2"	44 1/4"	44 1/4"	30 1/2"	44 1/4"	30 1/2"	44 1/4"	29 7/8"
<b>O V E N S</b>								
Self-Cleaning Electric Oven (4.3 cu. ft.)	.	.	.	.	.	.	.	.
Oven Size: 25" w x 16" h x 18 3/4" d								
Electric Self-Cleaning Convection Oven (4.0 cu. ft.)	optional	optional	optional	optional	optional			.
Oven Size: 25 w x 16" h x 18" d	standard on STE Models							
Gas Self-Cleaning Oven with waist high Broiler (4.0 cu. ft.)						.	.	
Oven Size: 25 w x 16" h x 18" d								
"Stay Hot" Food Warmer		.	.	.	.	.	.	.
Electronic Oven Control	.	.	.	.	.	.	.	.
Delayed Start Baking	.	.	.	.	.	.	.	.
Dual Element Baking	.	.	.	.	.			.
Vari. Temp. Broil	.	.	.	.	.	.	.	.
Door Activated Oven Light	.	.	.	.	.	.	.	.
Heavy Duty, Plated Oven Racks	.	.	.	.	.	.	.	.
Porcelain Enamel Broiler Pan	.	.	.	.	.	.	.	.
<b>R A N G E T O P S</b>								
Electric High-speed Radiant Elements under glass (ST)	optional	optional						
High-Speed Radiant Elements under glass with Electronic Control (STE)	optional	optional						
Gas: Sealed Surface Burners with cast grates			4	.	.	.	.	.
Converts to L.P. (Propane)			.	.	.	.	.	.
Ultra Temp™ Electric Cast Elements	optional	optional	optional					
Electric High Speed Radiant Elements under glass			optional					
Porcelain Enamel Work Surface (replaces two burners/elements)			optional				optional	
Electronic Spark with Re-ignition			.	.	.	.	.	.
Easy Clean Porcelain Top or Top Frame	.	.	.	.	.	.	.	.
Nickel Trimmed Range Top	.	.	.	.	.	.	.	.
<b>U P P E R C A B I N E T</b>								
350 CFM Exhaust Fan standard (recirculating and outside vent)	.	.	.	.	.	.	.	.
636 CFM In-line Exhaust blower optional (outside vent only)	optional	optional	optional	optional	optional	optional	optional	
Cooking Surface Light, Night Light	.	.	.	.	.	.	.	.
"Feather Touch" Tempered Glass Oven Control Panel	.	.	.	.	.	.	.	.
<b>P O W E R R A T I N G S</b>								
Power Source (208 to 250V) appliance rating	220V-35A	220V-50A	220V-30A	220V-20A	220V-20A	120V-5A	120V-6A	220V-30A
Gas Top Burners, 8,000* BTU			2	2	3	2	3	
Gas Top Burners, 12,000* BTU			1	1	2	1	2	
Superburner, 15,000* BTU			1	1	1	1	1	
* Ratings for liquid propane are approximately 10% lower								
Power Ratings NG (BTU's)			43,000	43,000	63,000	58,000	78,000	
Power Ratings LP (BTU's)			38,700	38,700	56,700	52,200	70,200	
Power ratings/oven burner NG (BTU's)						16,000	16,000	
Shipping Weight	375 lbs.	410 lbs.	420 lbs.	385 lbs.	425 lbs.	395 lbs.	435 lbs.	200 lbs.

### Range Overall Dimensions:

4 Burner Model: 30 1/2" wide x 67 7/8" high x 29 1/2" deep Six Burner Model: 44 1/4" wide x 67 7/8" high x 29 1/2" deep.

Our 30" models will fit into a 30 1/8" opening without cabinet alterations. Short leg models require a minimum opening of 30 3/4", and are 65 7/8" high.

All 220V ranges come with standard four wire range cords attached. NOTE: The new electrical standard, (Jan. 98) requires that a four wire range cord be used in all new construction. Please advise if a three wire range cord is required (used only in existing construction). The electrical receptacle and gas piping should be installed approximately 4" above the floor and 15" to the right of the left edge of the cabinet opening (as you are facing the opening).

### EXHAUST OUTLET LOCATION:

Height of duct opening from floor to center of opening is 62 1/4". (On short leg models that height is 60 1/4")

Width to center of duct opening on 30" models is 15 3/8". (The duct is located in the center of the range)

Width to center of duct opening on 45" models is 15 3/8" from the left side of the range.

### ALL DIMENSIONS ARE FOR PLANNING PURPOSES ONLY.

Consult installation instructions before cutting cabinets, countertops or exhaust outlet.

We reserve the right to make product changes as required without notice.